

# High Sensitivity Air Sampling Smoke Detector with Command Module

## ***FIRElink-400CM***



### Features

- ▶ High sensitivity provided by laser based forward light scatter for reliable early warning
- ▶ Four sampling pipes up to 200m (aggregate) in length (still air)
- ▶ False alarms reduced by unique dust discrimination
- ▶ RS485 communications for networking and remote communications
- ▶ Command Module allows control over other FIRElink units on network

### Description

Model FIRElink-400CM is designed to provide very high sensitivity smoke detection using an aspirating technique. A unique sensing technology ensures that the detector operates at optimum sensitivity for the protected environment, without the need for complex set-up.

With the integrated Command Module this unit also provides a single location display, control and interfacing option for systems of up to 127 detectors and allow global programming of all detector functions simultaneously.

### Specification

Order Code	FIRElink-400CM (Standard Detector with Command Module)
Supply Voltage	21.6V - 26.4Vd.c.
Current Consumption	920mA @ 24V DC at fan speed 8
Relay Contact Rating	500mA @ 30V
Operating Temperature Range	0 to +38°C (UL268), -10 to + 60°C (CEA4022)
Operating Humidity Range	0 - 90% non-condensing
Measurement Range (%Obs/m)	0.0015% to 25%
Detection Principle	Laser light scattering mass detection and particle evaluation
Particle Sensitivity Range	0.003µ to 10µ
Dust Discrimination Principle	3D <sup>3</sup> Laser Dust Discrimination (LDD)
Maximum Single Sampling Pipe Length / Diameter	100 / ¾" nominal bore (27mm O/D)
Recommended Number of Sampling Holes (EN54-20 performances) Per Inlet	Class A - 2 holes
	Class B - 6 holes
	Class C - 10 holes
Total Sampling Pipe Maximum	200m @ 100 sampling holes
Alarm Levels	4 (Aux, Pre-alarm, Fire 1 and Fire 2)
IP Rating	IP50
Sampling Pipe Inlets	4 on top, 4 at rear
Exhaust Air Pipe Outlets	1 on top, 1 at rear
Weight(kg) / Size(mm)	5.3 / H372 x W427 x D95

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.