

Conventional Alarm Bells

MBF-6EV and *MBA-6*



MBF-6EV Features

- ▶ Low Profile
- ▶ Low current consumption
- ▶ Fully suppressed and polarised
- ▶ 95dB(A) at 1 metre
- ▶ Simple installation with multi-fixing base plate

MBF-6EV Description

The MBF-6EV is a six inch diameter internal use Conventional Alarm Bell based upon the industry standard KOBELL range.

MBA-6 Features

- ▶ Low Profile
- ▶ Low current consumption
- ▶ Fully suppressed and polarised
- ▶ 95dB(A) at 1 metre
- ▶ Weatherproof for external installation
- ▶ Simple installation with multi-fixing base plate

MBA-6 Description

This six-inch diameter bell unit has the same operation as the MBF-6EV except it comes equipped with a weatherproof back box enabling it to be used externally.

Specifications		
Ordering Codes	MBF-6EV	MBA-6
Operating Voltage	19.2 - 28.8 Vdc	
Rated Current ($\pm 20\%$)	11mA	12mA
Operating Temperature Range	-10°C to + 50°C	
Maximum Humidity	45-85% Non Condensing (at 40°C)	
Gong Colour	Red	
Gong Material	Aluminium	
Maximum Sound Output	95dB(A) at 1 metre	
Weight (g) / Diameter (mm) / Depth (mm)	410 / 150 / 53 (inc back box)	820 / 150 / 104 (inc back box)